
## 2.5" WATER TEST GAUGES COPPER ALLOY BOURBON TUBE AND SOCKET MODEL 25TPHOSE & 25TPHOSE-MAX



Utility water test gauge with or without maximum indicating pointer. For pressure tests of residential and commercial water lines.

## STANDARD FEATURES

- 2.5" dial size
- Copper Alloy Bourbon tube and swivel connection
- Black plastic case
- 3/4" swivel connection, top mount
- Plastic lens
- Accuracy: 3/2/3% per ASME B40.1 Grade B
- White scale with black graduations and numerals
- Range: 0/300 PSI



300 270 30 240 psi 90 180 150 120
and the second second second

25TPHOSE-MAX

**MODEL 25TPHOSE** 

MODEL #	Unit	Α	В	С	D	Е	F
25TPHOSE	ln.	2.52"	1.11"	1.18"	0.58"	0.81"	
	mm	64	28	30	15	21	N/A
25TPHOSE-MAX	ln.	2.52"	1.11"	1.18"	0.58"	0.81"	0.20"
	mm	64	28	30	15	21	5

## STANDARD RANGE

RANGE	CODE	FIGURES	GRADUATIONS
0/300 PSI	PG	30 PSI	3 PSI

HOW TO ORDER - PLEASE SPECIFY THE FOLLOWING:				
MODEL #	RANGE	OPTIONS		
25TPHOSE	PG	MAX = Maximum Indicating Pointer		

Customer		
Project		
Engineer		
PRO or P.O. #	_	

Weksler Glass Thermometer Corporation 3295 Cobb International Blvd. • Kennesaw, GA 30152 Telephone: 888-650-6923 • Fax: 770-429-0795 E-mail: Sales@WekslerGlass.com • Website: www.WekslerGlass.com