


PRESSURE/TEMPERATURE PLUGS

MODEL PT25NOR, EXT, NEO


MODEL PT50NOR, EXT, NEO

ACCESSORIES


MODEL PT25NOR
(1/4" NPT)




MODEL PT25NOR PBF
(1/4" NPT)




MODEL PT25NEO
(1/4" NPT)




MODEL PT25EXT1.75
(1/4" NPT)




MODEL PT25NOR-3XL
(1/4" NPT)




MODEL PT25NEO-3XL
(1/4" NPT)




MODEL PT50NOR
(1/2" NPT)




MODEL PT50NOR PBF
(1/2" NPT)




MODEL PT50NEO
(1/2" NPT)




MODEL PT50EXT1.75
(1/2" NPT)



MODEL PT50NOR-3XL
(1/2" NPT)



MODEL PT50NEO-3XL
(1/2" NPT)



PT Plugs	Body Material	Connection Size	Core	Max Temp	Max Pressure
PT25NOR	BRASS	1/4"	NORDEL	350 DEG F	1,500 PSI
PT25NOR-PBF	LEAD FREE BRASS	1/4"	NORDEL	350 DEG F	1,500 PSI
PT25NEO	BRASS	1/4"	NEOPRENE	200 DEG F	1,500 PSI
PT25NOR-3XL	BRASS	1/4"	NORDEL	350 DEG F	1,500 PSI
PT50NOR	BRASS	1/2"	NORDEL	350 DEG F	1,500 PSI
PT50NOR-PBF	LEAD FREE BRASS	1/2"	NORDEL	350 DEG F	1,500 PSI
PT50NEO	BRASS	1/2"	NEOPRENE	200 DEG F	1,500 PSI
PT50NOR-3XL	BRASS	1/2"	NORDEL	350 DEG F	1,500 PSI

PTEXT Standard Features:

- PT Plug extensions for use with P/T
- Plugs on insulated pipe
- Brass, 1.75" overall length

PTNOR Standard Features:

- Brass body
- Nordel core (dual core design)
- Plastic cap retainer
- Maximum pressure 1,500 PSI
- Operational temp. range 45° F to 150° F

PTNEO Standard Features:

- Brass body
- Neoprene core
- Plastic cap retainer
- Maximum pressure 1,500 PSI
- Operational temp. range 45° F to 50° F

Accessories	Description	Material	Connection Size	Length
PT25EXT1.75	EXTENDER	BRASS	1/4"	1 3/4"
PT50EXT1.75	EXTENDER	BRASS	1/2"	1 3/4"
PT25EXT1.75-PBF	EXTENDER	LEAD FREE BRASS	1/4"	1 3/4"
PT GAUGE ADAPTER	GAUGE ADAPTER	SS	0.0125	1 3/4"



Three Pressure Temperature (P/T) Kits to Choose From:

1. P/T Kits to Source and Stock-Suggested Part Number- WGTC MODEL # PTC-25-100

- (1) PT Case - Heavy duty plastic with foam insert
- (1) 2 1/2" Pressure gauges - Catalog No. 25TL4PDW-PBF
- (2) 1" Pocket thermometers- Catalog No. 1BK0507/ B1B5-D and Catalog No. 1BK0515-B1B5-H
- (1) Gauge adapter - Catalog No. PT Gauge Adapter

2. P/T Kits to Source and Stock-Suggested Part Number-WGTC MODEL # PTC-25-200

- (1) PT Case - Heavy duty plastic with foam insert
- (1) 2 1/2" Pressure gauges - Catalog No. 25TL4PGW-PBF
- (2) 1" Pocket thermometers- Catalog No. 1BK0507/ B1B5-D and Catalog No. 1BK0515-B1B5-H
- (1) Gauge adapter - Catalog No. PT Gauge Adapter

3. P/T Kits to Source and Stock-Suggested Part Number- WGTC MODEL # PTC-25-300

- (1) PT Case - Heavy duty plastic with foam insert
- (1) 2 1/2" Pressure gauges - Catalog No. 25TL4PGW-PBF
- (2) 1" Pocket thermometers- Catalog No. 1BK0507/ B1B5-D and Catalog No. 1BK0515-B1B5-H
- (1) Gauge adapter - Catalog No. PT Gauge Adapter

Test Kits	Dial Size	Pressure Range
PTC-25-100	2 1/2"	0-100 PSI
PTC-25-200	2 1/2"	0-200 PSI
PTC-25-300	2 1/2"	0-300 PSI

Customer _____

Project _____

Engineer _____

PRO or P.O. # _____